

# Supported HTML and CSS for the Amazon Kindle

## *Miscellaneous Tags*

<code>&lt;!--...--&gt;</code>	Comment. Not displayed in the book. (page 92)
<code>&lt;a href=""&gt; ...&lt;/a&gt;</code>	Links to a bookmark anchor ("#bookmarkname") or to an external website. (page 89)
<code>&lt;a name=""&gt; ...&lt;/a&gt;</code>	Establishes an internal bookmark to which you can link. (page 89)
<code>&lt;html&gt;...&lt;/html&gt;</code>	The opening and closing tags in your document.
<code>&lt;head&gt;...&lt;/head&gt;</code>	Contains information about the HTML document, such as <code>&lt;link&gt;</code> , <code>&lt;title&gt;</code> , and <code>&lt;style&gt;</code> tags.
<code>&lt;body&gt;...&lt;/body&gt;</code>	Contains the contents of the book.
<code>&lt;hr /&gt;</code>	Creates a line (horizontal rule). (page 91)
<code>&lt;img src="" alt="" /&gt;</code>	Inserts an image. (page 74)
<code>&lt;mbp:pagebreak/&gt;</code>	Page break. (page 92)

## *Font Formatting*

### Font Size

<code>&lt;small&gt;...&lt;/small&gt;</code>	Reduces font size to one level smaller than the current font size. (page 44)
<code>&lt;big&gt;...&lt;/big&gt;</code>	Increases font size to one level larger than the current font size. (page 42)

### Italics

<code>&lt;i&gt;...&lt;/i&gt;</code>	Italic. (page 43)
<code>&lt;em&gt;...&lt;/em&gt;</code>	Emphasized text (italicized). (page 43)
<code>&lt;cite&gt;...&lt;/cite&gt;</code>	Indicates that enclosed text is quoted from another source (italicized).
<code>&lt;var&gt;...&lt;/var&gt;</code>	Indicates a variable name or program argument (italicized).

## Bold

<code>&lt;b&gt;...&lt;/b&gt;</code>	Bold (page 43)
<code>&lt;strong&gt;...&lt;/strong&gt;</code>	Strong emphasis (bold). (page 43)

## Lines

<code>&lt;u&gt;...&lt;/u&gt;</code>	Underlined. (page 44)
<code>&lt;s&gt;...&lt;/s&gt;</code>	Strikethrough. (page 46)
<code>&lt;strike&gt;...&lt;/strike&gt;</code>	Strikethrough. (page 46)

## Mono-spaced

<code>&lt;code&gt;...&lt;/code&gt;</code>	Computer code. (page 47)
<code>&lt;kbd&gt;...&lt;/kbd&gt;</code>	Keyboard text. (page 47)
<code>&lt;samp&gt;...&lt;/samp&gt;</code>	Sample text. (page 47)
<code>&lt;tt&gt;...&lt;/tt&gt;</code>	Teletype text. (page 47)

## Other

<code>&lt;span&gt;...&lt;/span&gt;</code>	Generic tag; can be used to apply a variety of styles. (page 47)
<code>&lt;sub&gt;...&lt;/sub&gt;</code>	Reduces the font size and drops the text below the baseline. (page 45)
<code>&lt;sup&gt;...&lt;/sup&gt;</code>	Reduces the font size and raises the text to the top of the line. (page 45)

## Paragraphs, etc.

<code>&lt;h1&gt;...&lt;/h1&gt;</code>	Heading tags. (page 67)
<code>&lt;h2&gt;...&lt;/h2&gt;</code>	
<code>&lt;h3&gt;...&lt;/h3&gt;</code>	
<code>&lt;h4&gt;...&lt;/h4&gt;</code>	
<code>&lt;h5&gt;...&lt;/h5&gt;</code>	
<code>&lt;h6&gt;...&lt;/h6&gt;</code>	
<code>&lt;div&gt;...&lt;/div&gt;</code>	Division or section. (page 59)
<code>&lt;p&gt;...&lt;/p&gt;</code>	Paragraph. (page 48)

<code>&lt;blockquote&gt;...&lt;/blockquote&gt;</code>	Long quote. Creates left margin of 0.5 inches. (page 59)
<code>&lt;br /&gt;</code>	Line break. (page 58)
<code>&lt;center&gt;...&lt;/center&gt;</code>	Centers content horizontally. (page 55)
<code>&lt;ol&gt;...&lt;/ol&gt;</code>	Numbered list. Use <code>&lt;li&gt;</code> tags inside. (page 63)
<code>&lt;ul&gt;...&lt;/ul&gt;</code>	Bulleted list. Use <code>&lt;li&gt;</code> tags inside. (page 63)
<code>&lt;li&gt;...&lt;/li&gt;</code>	List item. (page 63)

### ***Common Attributes in HTML Tags***

class	Allows you to set a style in the style sheet to be used in multiple tags
name	Used in <code>&lt;a&gt;</code> tags to assign a bookmark name. (page 89)
width	Adjusts the first-line indent of a paragraph, blockquote, heading, and list tags. Negative creates a hanging indent. Supports pixels ( <code>width="30"</code> ), points ( <code>width="10pt"</code> ), percent ( <code>width="10%"</code> ), or <i>em</i> -units ( <code>width="3em"</code> ). (page 51)
height	Sets a top margin on a paragraph, blockquote, heading, and list tags. Supports pixels ( <code>height="30"</code> ), points ( <code>height="10pt"</code> ), percent ( <code>height="10%"</code> ), or <i>em</i> -units ( <code>height="3em"</code> ). (page 68)
style	Allows the inclusion of CSS styles in a specific tag.
align	Aligns the text in paragraph, blockquote, heading, and list tags. Supports values of left, right, and center.

### ***Supported CSS***

#### **Font**

Property	Description	Values
font-size	Sets the size of a font	xx-small
		x-small
		small
		medium
		large
		x-large

		xx-large
		<i>length</i>
		%
font-style	Sets the style of the font	normal
		italic
		oblique
font-weight	Sets the weight of a font	normal
		bold

## Positioning

Property	Description	Values
vertical-align	Sets the vertical alignment of an element	sub
		super

## Text

Property	Description	Values
text-align	Aligns the text in an element	left
		right
		center
		justify
text-decoration	Adds decoration to text	underline
		line-through
text-indent	Indents the first line of text in an element	<i>length</i>
		%